


# 

# USA / Canada - Panel Mounted Fuseholders, 571/572 Series



#### **571 Series Panel Mounted Fuseholders**

Panel mount fuseholders are available for supplementary or Class CC branch circuit protection. Class CC fuses have a rejection feature on one end cap which mates with the rejection feature of Littelfuse Class CC fuse blocks and fuseholders to prevent the installation of fuses with lower voltage ratings or interrupting ratings. Watertight version must be front panel mounted.



**Mounting Hole** 

### **Ordering Information**

Part N	lumber	Bottom	Fuse Length	For Use
Standard	Watertight	Terminal	Range*	With
<b>571</b> 027	<b>571</b> 027P	Straight	15/16" - 13/8"	Midget Fuses
<b>571</b> 028	<b>571</b> 028P	Rt. Angle		
<b>571</b> 007	<b>571</b> 007P	Straight	113/32" - 11/2"	Midget Fuses
<b>571</b> 008	<b>571</b> 008P	Rt. Angle		
<b>571</b> OCC	<b>571</b> OCCP	Straight	1½"	Class CC Fuses
<b>571</b> RCC	<b>571</b> RCCP	Rt. Angle		

\*Fuse diameter is 13/32".

Note: Contact the factory for versions with pre-assembled wire leads.

**O-Rings:** 901-184 (body) 901-260 (knob)

#### **Specifications**

**Voltage Rating:** 600 Volts

**Ampere Rating:** 30 amperes for Class CC and

> Midget fuses 4000 Volts

Dielectric strength:

Terminals: Tin-plated brass combination solder

and quick-connect

Molded parts: Black thermoplastic Approvals:

UL Recognized (File No. E14721) — 571 series UL Recognized for branch circuit protection


--- 571 OCC/RCC

CSA Certified (File No. LR7316)



#### **572 Series Panel Mounted Fuseholders**

The 572 series panel mount fuse holders are designed to minimize installation time. The unique design incorporates a snap-mount feature that allows the holder to be installed without any tools or mounting hardware



## **Ordering Information**

Part Number		Bottom	Fuse Length	For Use With
Standard	Watertight	Terminal	Range*	rui ose with
<b>572</b> 027	<b>572</b> 027P	Straight	1 <sup>5</sup> / <sub>16</sub> " — 1 <sup>3</sup> / <sub>8</sub> "	Midget Fuses
<b>572</b> 028	<b>572</b> 028P	Rt. Angle		
<b>572</b> 007	<b>572</b> 007P	Straight	113/32" - 11/2"	Midget Fuses
<b>572</b> 008	<b>572</b> 008P	Rt. Angle		
<b>572</b> OCC	<b>572</b> OCCP	Straight	1½"	Class CC Fuses
<b>572</b> RCC	<b>572</b> RCCP	Rt. Angle		

<sup>\*</sup>Fuse diameter is 13/32"

Note: Contact the factory for versions with preassembled wire leads.

#### **Specifications**

**Voltage Rating:** 

**Ampere Rating:** 30 Amperes for Class CC and Midget fuses

**Dielectric Strength:** 4000 Volts

Terminals: Tin-plated brass combination solder and quick-connect

**Molder Parts:** Black thermoplastic

UL Recognized (File No. E14721) - 572 Series Approvals:

UL Recognized for branch circuit protection - 571 OCC/RCC CSA Certified (File No. LR7316)

Mounting: Designed to fit 14-18 gauge panels with Double

"D" punch or 0.875" knock-out hole.