

## Task Lighting

### Hand Lamps & Cord Reels



## General Purpose Cord Reel Lights

Conveniently mounts on wall or ceiling to handle all light-to-medium-duty incandescent task lighting needs. Cord locks at desired working length, and retracts with a slight tug. Sturdy steel housing, 2-ft. installation cord. Lamp not included. No. **2V563** rough service lamp (75W) is recommended.

### CORD REEL LIGHTS

Comfortable handle has convenient tool tap outlet and dependable push-button switch. UL Listed. Nos. **1A135** and **6X756** have grounded handles with a 7-amp resettable circuit breaker, and are CSA Certified. No. **1W943** is also CSA Certified.

### CORD REEL WITH MAGNETIC LIGHTS

Powerful magnetic swivel base on light attaches to any nearby ferrous metal surface—brings light close to where you need it. Easy to aim for hands-free use.

### SPECIAL PURPOSE REEL LIGHT

Light automatically goes on when cord is pulled from reel. Meets OSHA requirements for commercial garage use when lamp and cord cannot reach within 18" of the floor. NEC Article 511 (f). 125V, 60 Hz. UL Listed.

WARNING: Not for use in hazardous or explosive locations.

Description	Gauge/Conductors	Cord	Guard	Cord Length (Ft.)	Max. Amps*	Housing Dia. (In.)	Brand	Stock No.	Each	Shpg. Wt.
Cord Reel Light	18/3	SVT	Steel	20	7	6½		<b>1A135</b>		4.0
Cord Reel Light	18/3	SVT	Steel	50	7	9½		<b>6X756</b>		9.6
Cord Reel Light	16/3	SJT	Steel	25	10	9½		<b>1W943</b>		9.5
Cord Reel Light w/Magnet	18/3	SVT	Steel	20	—	6½		<b>4DU82</b>		5.7
Cord Reel Light w/Magnet	18/3	SVT	Steel	20	7	6½		<b>5XN06</b>		4.8
Special Purpose	18/3	SJT	Thermoplastic	35	5	9½		<b>6X755</b>		8.5

(\*) Represents total of lamp and other devices plugged into reel lamp.



## General Purpose Multi-Outlet Cord Reels

### 3-OUTLET

Pulls out and locks at desired working length; automatically retracts with a slight pull of cord. 3 grounded female outlets on a molded tap. 9½" dia. steel housing swivel mounts on wall or ceiling. Complete hardware included. Has a 2-ft. installation cord. 125V. CSA Certified.

### 4-OUTLET

Features a carrying handle, circuit breaker protection, and 4 grounded female outlets. 125V, 60 Hz.

WARNING: Not for use in hazardous or explosive locations.

### 2-OUTLET GFCI

Features resettable ground fault circuit interrupter for added safety. Shatter-resistant case. UL Listed at 15 amps, 125V, 60 Hz.

### RESETTABLE, CIRCUIT BREAKER PROTECTED RETRACTABLE

Reels automatically retract with pull. Feature 3 grounded outlets. 125V, 60 Hz. No. **3V950** is CSA Certified, No. **4XP67** has 14-ga. wire.

Description	Gauge/Conductors	SJT Cord Length (Ft.)	Max Amps	Stock No.	Each	Shpg. Wt.
3-Outlet Reel	16/3	30	10	<b>1A136</b>		8.4
4-Outlet Reel	16/3	25	10	<b>3A535</b>		3.6
2-Outlet GFCI Reel	14/3	20	15	<b>6VW60</b>		4.0
Circuit Breaker Reel	16/3	30	10	<b>3V950</b>		11.0
Circuit Breaker Reel	14/3	30	13	<b>4XP67</b>		9.1