









Document	Catalog No. / Katalog-Nr.	Description / Beschreibung	Weight/ea	VPE/Pack	U/M	EDP-No.
1827	Flush Mounting Receptacles					
 <p>S-1660 CZ</p> <p>S-1656 CZ</p>	S-1656 CZ	Flush mount receptacle, 2-pole 3-wire grounding, 25 Amp, 250Vac, NBR 6147 - NEMA 1516, thermoplastic, gray	30g	1000	ea	110827
	S-1660 CZ	Wallplate, light gray, to fit Cat. # S-1656 CZ (or for replacement use)	20g	1000	ea	110829
	S-1666 CZ	Flush mounting receptacle Catalog No. S-1656 CZ with S-1660 CZ	50g	1000	ea	110799
Further informations can be found in documents indicated.						
2001	Snap-In Receptacles					
 <p>S-1657/M</p>	S-1657/M	Snap-in receptacle, 2-pole, 3-wire grounding, 25 Amp, 250Vac, NBR 6147 - NEMA 1516, thermoplastic, black, with 6.3 mm quick-connect terminals	17g	2000	ea	110800
	S-1658	Same as above, but with lead wires 150 mm long, stripped 5 mm, 0.75mm ² , 250Vac, 70°C	42g	1000	ea	102597
Further informations can be found in documents indicated.						
1828	Multiple Power Blocks					
 <p>S-30.6NSC</p>	S-30.6NS	Multiple Power Block with 6-outlets, 2-pole 3-wire grounding, 25 Amp, 250Vac, NBR 6147 - NEMA 1516, thermoplastic, with 3 m power supply cord, with plug	915g	40	ea	110826
	S-30.6NSC	Same as above, but with LED, fuse and switch	1000g	40	ea	110825
Further informations can be found in documents indicated.						
1933	Duplex Surface Mounting Receptacle Box					
 <p>SM-63306N</p>	SM-63306N	Duplex surface mounting receptacle box, 2-pole 3-wire grounding, 25 Amp, 250Vac, NBR 6147 - NEMA 1516, thermoplastic (ABS), with screw terminals	330g	100	ea	110833
Further informations can be found in documents indicated.						
1831	Single Flush Mounting Receptacles for Wet Locations					
 <p>S-2058 CZ</p>	S-2057 CZ	Single flush mounting receptacle for wet locations with self-closing lid, thermoplastic, gray, 2-pole 3-wire grounding, 25 Amp, 250Vac, NBR 6147 - NEMA 1516, with 6.3 mm quick-connect terminals	55g	500	ea	110798
	S-2058 CZ	Same as above, but with lead wires 260 mm long, stripped 5 mm, 0.75mm ² , 250Vac, 70°C	67g	500	ea	110832
Further informations can be found in documents indicated.						
1830	Single Surface Mounting Receptacles for Wet Locations					
 <p>S-2157 CZ</p>	S-2157 CZ	Single surface mounting receptacle for wet locations with self-closing lid, thermoplastic, gray, 2-pole 3-wire grounding, 25 Amp, 250Vac, NBR 6147 - NEMA 1516, with 6.3 mm quick-connect terminals	90g	400	ea	110797
	S-2158 CZ	Same as above, but with lead wires 260 mm long, stripped 5 mm, 0.75mm ² , 250Vac, 70°C	102g	400	ea	110830
Further informations can be found in documents indicated.						
1829	Duplex Surface Mounting Receptacles for Wet Locations					
 <p>S-426</p>	S-426	Duplex surface mounting receptacle for wet locations with self-closing lids, thermoplastic, 2-pole 3-wire grounding, 25 Amp, 250Vac, NBR 6147 - NEMA 1516, with 6.3 mm quick-connect terminals	300g	150	ea	110831
Further informations can be found in documents indicated.						
1697	Mains Line Round or Flat Plugs without Earthing Contact					
 <p>612-K</p>	612-K WH	(KEMA) Round plug, 6 Amp, 4 mm round pins, thermosetting plastic type 31/131.5, (BK) black, (WH) white and (GY) grey.	32g	80	ea	108057
	670-K WH	(Export only) Round plug, 6 Amp, 4 mm round pins, thermosetting plastic type 31/131.5, (BK) black and (WH) white.	22g	100	ea	108058
	692-K WH	(Export only) Flat plug, 6 Amp, 4 mm round pins, thermosetting plastic type 31/131.5, (BK) black and (WH) white.	17g	50	ea	108059