

Extra Flexible Conduit



6711 - 6718

4751 &
4755




4752 -
4754



Swivel Lok

4741 -
4748



UL(UR) Recognized (conduit);
UL Listed (fittings)
CSA Certified - C22.2 No. 18

Dimensions = mm (Nominal)

Trade Size	Conduit Ø		Bend Radius
	Inner	Outer	
3/8	12.4	17.8	50.8
1/2	16.0	21.1	76.2
3/4	21.1	26.4	101.6
1	26.7	33.0	127.0
1 1/4	35.6	41.9	160.0
1 1/2	40.4	47.8	190.5
2	51.6	59.9	254.0

Swivel Lok®

Swivel Lok, multi-position connector (sizes 1/2 to 1) twists from 0° to 90°, easing installation in difficult locations and eliminating need to stock other angle connectors.

Nonmetallic Extra Flexible Conduit and Connectors, Swivel Lok Multi-Position Connectors and 90 Degree Connectors for Extra Flexible Liquid-tight Nonmetallic Conduit.

All black nonmetallic construction ends metal fatigue and separation problems.

For use in dry or wet locations when the conduit and fittings are not subject to physical damage.

Use extra flexible conduit and connectors whenever added flexibility is required for installation, operation or maintenance.

Size	Conduit/Pack		Straight/Pack		Swivel Lok/Pack		90° Connector/Pack	
	Conduit	Length	Conduit	Length	Conduit	Length	Connector	Length
3/8	6711	30m	4741	25	--	--	4751	25
1/2	6712	30m	4742	25	4752	25	--	--
3/4	6713	30m	4743	25	4753	25	--	--
1	6714	30m	4744	10	4754	10	--	--
1 1/4	6715	30m	4745	10	--	--	4755	10
1 1/2	6716	15m	4746	5	--	--	--	--
2	6718	15m	4748	5	--	--	--	--