

UL CSA



125V, 60°C

Dimensions

= mm

A-8731

A-3631-1 or A3631-5

NEMA
5-15P

CEE 22

Anschlußleitung, ungeschirmt,
Stecker gerade, Kupplungsdose
gerade

Power Supply Cord, Unshielded,
Straight Plug, Straight Connector

Catalog No.	Wire	AWG	mm ²	No x Ø	CU kg/km	O.D. Ø	Length	Color	Amp	UPE
545■	SVT	18/3	3x0.82	41x0.160	BC 23	6.4	2.29m	Black	10	25
545B■	SVT	18/3	3x0.82	41x0.160	BC 23	6.4	2.29m	Black	10	100
535■	SVT	18/3	3x0.82	41x0.160	BC 23	6.4	2.31m	Black	10	25
535B■	SVT	18/3	3x0.82	41x0.160	BC 23	6.4	2.31m	Black	10	100
531■	SJT	18/3	3x0.82	41x0.160	BC 23	8.3	2.0m	Black	10	25
531B■	SJT	18/3	3x0.82	41x0.160	BC 23	8.3	2.0m	Black	10	100
532■	SJT	18/3	3x0.82	41x0.160	BC 23	8.3	3.0m	Black	10	25
532B■	SJT	18/3	3x0.82	41x0.160	BC 23	8.3	3.0m	Black	10	100
533■	SJT	16/3	3x1.31	65x0.160	BC 36	9.0	2.0m	Black	13	25
546■	SJT	16/3	3x1.31	65x0.160	BC 36	9.0	2.3m	Black	13	25
534■	SJT	16/3	3x1.31	65x0.160	BC 36	9.0	3.0m	Black	13	25
534B■	SJT	16/3	3x1.31	65x0.160	BC 36	9.0	3.0m	Black	13	100