



Dimensions = mm

5279-CWP

Industrial Grade Integrated Power Inlets and Outlets with Weather-Resistant Covers. Engineered to IP64 and NEMA 3R protection ratings. UL and NOM Listed, CSA Certified where applicable. Please request for further Informations !!!

Catalog No.	NEMA	AC-Rating	Description	Wght/ea	UPE/Pack	EDP-No
5278-CWP	5-15P	15A 125V	Flanged Inlet	227g	10	115064
5279-CWP	5-15R	15A 125V	Flanged Outlet	227g	10	115072
15678-CWP	6-15P	15A 250V	Flanged Inlet	227g	10	115065
15679-CWP	6-15R	15A 250V	Flanged Outlet	227g	10	115073
15378-CWP	5-20P	20A 125V	Flanged Inlet	227g	10	115068
15379-CWP	5-20R	20A 125V	Flanged Outlet	227g	10	115076
5478-CWP	6-20P	20A 250V	Flanged Inlet	227g	10	115069
5479-CWP	6-20R	20A 250V	Flanged Outlet	227g	10	115077
4716-CWP	L5-15P	15A 125V	Locking Flanged Inlet	227g	10	115066
4715-CWP	L5-15R	15A 125V	Locking Flanged Outlet	227g	10	115074
4586-CWP	L6-15P	15A 250V	Locking Flanged Inlet	227g	10	115067
4585-CWP	L6-15R	15A 250V	Locking Flanged Outlet	227g	10	115075