




U.S.A. Canada

Mountable on
35mm DIN-Rail

LPSC 002

Dimensions = mm

4-Poles = 70.10



POWR-SAFE "Dead Front" Holders

provide optimum protection to personnel. Indicating and non-indicating versions are available in 1, 2, 3, or 4 poles for Class CC and Midget fuses.

Approvals: UL Listed, CSA Certified,
IEC Type 2 Protection,
CE Certified

SPECIFICATIONS

Voltage Rating: 600 Volts
Ampere Rating: 30 Ampere
Interrupting Rating: 200 kA (Class CC)
100 kA (Midget)

Terminal Type: Pressure Plate
Wire Range: AWG 6 - AWG 14 CU
Material: Thermoplastic
Flammability Rating: 94V0

Poles	Class CC			Midget		
	Fuse Type	Non-Indicat	Indicating	Fuse Type	Non-Indicat	Indicating
1	Class CC	LPSC 001	LPSC 001 ID	Midget	LPSM 001	LPSM 001 ID
2	Class CC	LPSC 002	LPSC 002 ID	Midget	LPSM 002	LPSM 002 ID
3	Class CC	LPSC 003	LPSC 003 ID	Midget	LPSM 003	LPSM 003 ID
4	Class CC	LPSC 004	LPSC 004 ID	Midget	LPSM 004	LPSM 004 ID