



**DENMARK / DÄNEMARK**

**Rating: 13 Amp. 250 Volt AC**

Receptacle 2-Pole 3-Wire Grounding, Push-In Terminals (1.5 to 2.0 mm<sup>2</sup>), Tamper Resistant, Side Grips for Box Mounting, Protection IP 20

Steckdosen-Einsatz 2P+E, schraubloser Steckanschluss (1.5 bis 2.0 mm<sup>2</sup>), mit Kinderschutz, seitliche Krallen für Dosenmontage, Schutzklasse IP 20

Approvals: DEMKO

**ORDERING INFORMATION:**

Catalog No.	Color	Description	Weight/ea	Packed/VPE	EDP-No
501D6011	White	Receptacle, Box Mount	36g	100/10	119646
501D5011	Light Grey	Receptacle, Box Mount	36g	100/10	119649
500D6810	White	Frame (50x50x8.5)mm	5g	100/10	119651
500D5810	Light Grey	Frame (50x50x8.5)mm	5g	100/10	119652
500D6410	White	Frame (63x63x8.5)mm	11g	100/10	119654
500D5410	Light Grey	Frame (63x63x8.5)mm	11g	100/10	119655
500D6910	White	Frame (68x73x8.5)mm	19g	100/10	119656
500D5910	Light Grey	Frame (68x73x8.5)mm	19g	100/10	119657