



**Danish System**

Dänisches System

**FEATURES:**

- Rubber Body and Cover
- Pin Safety Contact
- Two Front Screws
- Cable Dia. up to 2.5 mm<sup>2</sup>
- Funnel-Cable Lead-In
- Protection IP 44
- Rating 13 Amp, 250 Volt AC

**DENMARK / DÄNEMARK**

**Rating: 13 Amp. 250 Volt AC**

Rubber Plug and Connector  
 2-Pole 3-Wire Grounding,  
 Pin Safety Contact, Two Front Screws,  
 Cable Diameter up to 2.5 mm<sup>2</sup>,  
 Funnel-Cable Lead-In, Protection IP 44

Vollgummi Stecker und Kupplung  
 2-polig + Erde, Stiftschutzkontakt,  
 2-fach Frontverschraubung,  
 Anschlussquerschnitt bis 2.5 mm<sup>2</sup>,  
 Trichter-Knickschutz, Schutzklasse IP 44

Approvals: DEMKO

**ORDERING INFORMATION:**

Catalog No.	Color	Description	Weight/ea	Packed/VPE	EDP-No
346GUC	Red/Green	Rubber Plug	103g	10	119542
356GUC	Red/Green	Rubber Connector	166g	10	124494
346GUC/SW	Black	Rubber Plug	103g	10	123015
356GUC/SW	Black	Rubber Connector	166g	10	119543