

General Purpose Quartz Floodlights

Floodlighting

TQ/TQE

Intended Use

For signs, landscaping and commercial or residential building facades.

Features

Housing – Compact, rugged, die-cast aluminum housing is ribbed for maximum heat dissipation. TQ has a die-cast aluminum doorframe, TQE lens attaches via tool-less clips. TQ1500 doorframe is die-cast aluminum with tool-less latch closure. Standard finish bronze polyester powder.

Installation – Adjustable mounting knuckle with 1/2" NPS threaded stem. Mounts to standard outlet boxes.

Optics – Anodized aluminum reflector with high efficiency and wide beamspread. Tempered glass lens with high temperature

gasketing. 500W models include double-ended quartz 500W lamp. 1500W models do not include double-ended quartz 1500W lamp.

Listings – UL Listed to U.S. and Canadian safety standards. UL/C-UL listed for wet locations.



Ordering Information

Example: **TQE 500 120 LPI**

Designation	Voltage	Options
Quartz TQE 500 TQ 500	120	(blank) Bronze (500W only) DWH White (500W only) LPI Lamp included (500W models)


Ordering Information

Example: **TQ 1500 L/LP**


Designation	Voltage	Options
Quartz TQ 1500	Determined by lamp (277V maximum)	L/LP Lamp NOT included (must be supplied by others.)

Dimensions are shown in inches (centimeters) unless otherwise noted.

	TQ 1500	TQE 500
Height	8.25 (20.96)	6.5 (16.51)
Width	13 (33.02)	8.875 (22.54)
Depth	6 (15.24)	3.5 (8.89)
Max. weight	6 lbs (2.72 kg)	2.07 lbs (.93 kg)



TQ 1500



TQ/TQE 500

FEATURES & SPECIFICATIONS

INTENDED USE

Ideal for applications where accurate color rendition is critical – signs, entry monuments, residential facades and landscaping.

CONSTRUCTION

Compact, rugged die-cast aluminum housing is ribbed for maximum heat dissipation. TQ has a die-cast aluminum doorframe, TQE lens attaches via tool-less clips. Finish is polyester powder paint for lasting durability.

OPTICAL SYSTEMS

Anodized aluminum reflector with high efficiency and wide beamspread. Tempered glass lens with high temperature gasketing to inhibit entrance of external contaminants.

Double-ended quartz lamp included in carton.

INSTALLATION



Adjustable mounting knuckle with 1/2" NPS threaded stem mounts to standard outlet boxes.

LISTING

UL/CUL listed suitable for wet locations (25° C maximum ambient temperature).

Floodlighting TQ/TQE

500W QUARTZ



Height: 6.5" (16.51 cm)
Width: 8.875" (22.54 cm)
Depth: 3.5" (8.89 cm)
Weight: 2.07lbs/.93 kg

ORDERING INFORMATION

Example: **TQE 500 120 LPI**

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories as separate catalog numbers (shipped separately).

Series	500	120	Options	LPI
TQE TQ	Wattage /Source 500	Voltage 120	(blank) Bronze (standard) DWH White	LPI

FEATURES & SPECIFICATIONS

INTENDED USE

Wide beamsread is ideal for signs, landscaping, and commercial or residential building facades.

CONSTRUCTION

Compact, rugged, die-cast aluminum housing is ribbed for maximum heat dissipation. Doorframe is die-cast aluminum with tool-less latch closure. Finish is dark bronze polyester powder paint for lasting durability.

OPTICAL SYSTEMS

Anodized aluminum reflector with high efficiency and wide beamsread. Tempered glass lens with high temperature gasketing to inhibit entrance of external contaminants.

Double-ended quartz 1500W lamp not included.
 (277V maximum)

INSTALLATION

Adjustable mounting knuckle with 1/2" NPS threaded stem — mounts to standard outlet boxes.


LISTING

UL/CUL listed suitable for wet locations (25°C maximum ambient temperature).

Floodlighting

TQ

1500W QUARTZ



Height: 8.25" (20.96 cm)
 Width: 13" (33.02 cm)
 Depth: 6" (15.24 cm)
 Weight: 6lbs/2.72 kg

ORDERING INFORMATION

Example: **TQ 1500 L/LP**

Choose the boldface catalog nomenclature that best suits your needs and write it on the appropriate line. Order accessories as separate catalog numbers (shipped separately).

TQ	1500	Voltage	L/LP
Series	Wattage /Source	Voltage	Lamp
TQ	1500	Determined by lamp (277V maximum)	L/LP Lamp NOT included. Must be supplied by others.