

3 CONDUCTOR LINE CORDS UNSHIELDED PVC

TYPE SJT
UL LISTED, CSA CERTIFIED

CORD APPLICATIONS:

- Business Machines
- Point-Of-Sale Terminals
- Computers and Peripheral Equipment
- OEM Equipment

CHARACTERISTICS

Operating Temperature:

- 65° C

Voltage Rating:

- 125 Volt


Color Description:

- Color Code: Black, White, Green
- Jacket Color: Gray

Product Description:

- Conductor: Stranded Bare Copper
- Insulation: Color-Coded PVC
- Jacket: PVC

3020-UL C-13 Style
Straight
Connector



Jacket Stripped
1.417" (36.0mm)
Insulation Stripped
0.236" (6.0mm)

3011-UL C-13 Style
Right Angle
Connector



Jacket Stripped
1.417" (36.0mm)
Insulation Stripped
0.236" (6.0mm)

UNSHIELDED - 3 CONDUCTOR - STRAIGHT PLUG

Part Number	Length		AWG	Conductor			Diameter		Power Watts	Rating Amps	Cord Type
	Ft.-in.	m		mm ²	Strand	mm	In.	mm			
3020 GRY	8-2.4	2.5	18	0.82	49/35	49x0.145	0.33	8.3	1250	10	SJT

UNSHIELDED - 3 CONDUCTOR - RIGHT ANGLE PLUG

Part Number	Length		AWG	Conductor			Diameter		Power Watts	Rating Amps	Cord Type
	Ft.-in.	m		mm ²	Strand	mm	In.	mm			
3011 GRY	8-2.4	2.5	18	0.82	49/35	49x0.145	0.33	8.3	1250	10	SJT

SPECIFICATIONS

- UL Standard 817
- UL Standard 62
- CSA C22.2 No. 21
- CSA C22.2 No. 49
- EN 60320/C13
- IEC 320/C13
- VDE 0625/C13



LISTED



Certified

Canadian Standards Association

AVAILABILITY

- 100 Piece Packages
- Special Made to Order Length

