



Liquidtight Nonmetallic/Nylon Straight and 90 Degree Strain Relief Cord Connectors:

- For use in wet or dry locations to provide a liquidtight and strain relief termination for flexible cord and cable.
- Black Nylon construction is lightweight and easy to use, Neoprene grommet, Resists most common industrial corrosives, Color-coded GOTCHA® ring provides fast identification of cord size.



Document	Catalog No. / Katalog-Nr.	Hubs	Cable Ø	Color-Code	A	B	C	D	E	Form	Weight/ea	VPE/Pack	U/M	EDP-No.
Series 47xx NPT, Straight Cord Connectors, Nonmetallic/Nylon, Black														
	4699-2*	1/4"	3.2 - 4.8	Orange	25.0	11.1	27.8	8.3	---	F1	23g	25	ea	101081
	4699-3*	1/4"	4.8 - 6.4	Red	25.0	11.1	27.8	8.3	---	F1	23g	25	ea	101082
	4699-4*	1/4"	6.4 - 7.9	Black	25.0	11.1	27.8	8.3	---	F1	23g	25	ea	101083
	4700-4*	3/8"	6.4 - 7.9	Black	25.0	11.1	27.8	11.1	---	F1	23g	25	ea	101089
	4700-5	3/8"	7.9 - 9.5	White	25.0	11.1	27.8	11.1	---	F1	23g	25	ea	101090
	4700-6	3/8"	9.5 - 11.1	Blue	25.0	11.1	27.8	11.1	---	F1	23g	25	ea	101091
	4702-1	1/2"	1.6 - 3.2	Green	31.8	13.5	38.1	14.7	---	F2	35g	25	ea	101092
	4702-2	1/2"	3.2 - 4.8	Orange	31.8	13.5	38.1	14.7	---	F2	39g	25	ea	101093
	4702-3	1/2"	4.8 - 6.4	Red	31.8	13.5	38.1	14.7	---	F2	35g	25	ea	101094
	4702-4	1/2"	6.4 - 9.5	White	31.8	13.5	38.1	14.7	---	F2	35g	25	ea	101095
	4702-5	1/2"	9.5 - 12.7	Blue	31.8	13.5	38.1	14.7	---	F2	36g	25	ea	101096
	4702-6	1/2"	12.7 - 15.9	Brown	31.8	13.5	38.1	14.7	---	F2	30g	25	ea	101097
	4703-1	3/4"	9.5 - 12.7	Blue	37.7	13.9	41.3	19.5	---	F3	55g	15	ea	101098
	4703-2	3/4"	12.7 - 15.9	Brown	37.7	13.9	41.3	19.5	---	F3	51g	15	ea	101099
4703-3	3/4"	15.9 - 19.0	Yellow	37.7	13.9	41.3	19.5	---	F3	53g	15	ea	101100	
4703-4	3/4"	19.0 - 22.2	Purple	37.7	13.9	41.3	19.5	---	F3	44g	15	ea	101101	
4704-3	1"	15.9 - 19.0	Yellow	46.8	17.5	44.5	25.8	---	F4	79g	10	ea	101104	
4704-4	1"	19.0 - 22.2	Purple	46.8	17.5	44.5	25.8	---	F4	77g	10	ea	101105	
4704-5	1"	22.2 - 25.4	Grey	46.8	17.5	44.5	25.8	---	F4	71g	10	ea	101106	
4704-6	1"	25.4 - 28.6	Pink	46.8	17.5	44.5	25.8	---	F4	65g	10	ea	101107	

Series 47xx NPT, 90° Cord Connectors, Nonmetallic/Nylon, Black														
	4792-2*	1/2"	3.2 - 4.8	Orange	31.8	13.5	14.7	63.5	35.7	F2	41g	25	ea	101142
	4792-3	1/2"	4.8 - 6.4	Red	31.8	13.5	14.7	63.5	35.7	F2	41g	25	ea	101143
	4792-4	1/2"	6.4 - 9.5	White	31.8	13.5	14.7	63.5	35.7	F2	41g	25	ea	101144
	4792-5	1/2"	9.5 - 12.7	Blue	31.8	13.5	14.7	63.5	35.7	F2	40g	25	ea	101145
	4792-6	1/2"	12.7 - 15.9	Brown	31.8	13.5	14.7	63.5	35.7	F2	38g	25	ea	101146
	4793-2	3/4"	12.7 - 15.9	Brown	37.7	13.9	19.5	71.0	42.1	F3	63g	15	ea	101148
	4793-3	3/4"	15.9 - 19.0	Yellow	37.7	13.9	19.5	71.0	42.1	F3	60g	15	ea	101149
	4793-4	3/4"	19.0 - 22.2	Purple	37.7	13.9	19.5	71.0	42.1	F3	58g	15	ea	101150
	4794-3	1"	15.9 - 19.0	Yellow	46.8	17.5	25.8	83.7	50.4	F4	99g	10	ea	101153
	4794-4	1"	19.0 - 22.2	Purple	46.8	17.5	25.8	83.7	50.4	F4	96g	10	ea	101154
4794-5	1"	22.2 - 25.4	Grey	46.8	17.5	25.8	83.7	50.4	F4	85g	10	ea	101155	

* If current stock is depleted, item will be discontinued.

Product Features

- Black Nylon construction is lightweight and easy to use.
- Neoprene grommet.
- Resists most common industrial corrosives.
- Color-coded GOTCHA® ring provides fast identification of cord size.
- Use optional standard locknuts, sealing locknuts, sealing washers and bonding locknuts (available on request) to complete a liquidtight installation on a sheet box or panel.
- UL Listed - Standard 514B

