


20A 125V; 20A 250V

Hospital & Industrial Grade



ELECTRICAL		
DIELECTRIC VOLTAGE	CURRENT INTERRUPT.	TEMP. RISE
Withstands 2000V per UL 498	Full rated current	Max 30°C after 250 cycles of overload at 200% of rated current

MECHANICAL			
TERMINAL I.D.	TERMINAL ACCOMM.	PRODUCT I.D.	CORD GRIP RANGE
Brass, hot Grounding White, neutral	#18 - #10 AWG	Ratings & NEMA I.D. permanently marked on device	.245" - .700"
ENVIRONMENTAL			
FLAMMABILITY		OPERATING TEMP.	
Rated V-2 per UL 94		-40°C to 60°C	

STANDARDS & CERTIFICATIONS					
NEMA WD-6	ANSI C-73	UL 498	UL Fed Spec Listed WC-596	CSA C22.2 No. 42	NOM
✓	✓	✓	#E13393	#LR-406	#057



TYPE	PLUG	CONNECTOR	ANGLE PLUG	ANGLE CONNECTOR	FLANGED INLET	FLANGED OUTLET
20A 125V, NEMA 5-20P AND 5-20R, 2-P 3-W						
Industrial Grade						
Black & White	5366-C	5369-C	5366-CA	5369-CA	-	-
Yellow & White	5366-CY	5369-CY	-	-	-	-
Gray	5366-CG	5369-CG	-	-	-	-
All White	-	-	-	-	15378-C	15379-C
Hospital Grade						
Black & White	8315-C	8319-C	-	-	-	-
Transparent	8315-CT	8319-CT	8315-CAT	-	-	-
Power Light Transparent	8315-PLC	8319-PLC	-	-	-	-
20A 250V, NEMA 6-20P AND 6-20R, 2-P 3-W						
Industrial Grade						
Black & White	5466-C	5469-C	-	-	-	-
Transparent	-	-	8415-CAT	-	-	-
Yellow & White	5466-CY	5469-CY	-	-	-	-
All White	-	-	-	-	5478-C	5479-C

Power Light Plug & Connector

TYPE	PLUG	CONNECTOR
20A 125V, NEMA 5-20P & 5-20R, 2-P 3-W		
Factory Installed Green Light Indicates Power Status		
Black & White	5366-PLC	5369-PLC
All Black	5366-PLB	5369-PLB

Thermoplastic Elastomer Boots for 20A 2-P 3-W Devices

TYPE	PLUG BOOT	CONNECTOR BOOT
Black Yellow	6017 6017-Y	6018 6018-Y

