

## Hospital Grade Plugs and Connectors

2 Pole, 3 Wire Grounding  
 NEMA 5-15, 15A 125V  
 NEMA 6-15, 15A 250V  
 NEMA 5-20, 20A 125V  
 NEMA 6-20, 20A 250V



### Thermoplastic Hospital Grade Plugs and Connectors

#### FEATURES

- High impact-resistant thermoplastic housings.
- Assembly screws are speed-threaded and captive, reducing installation time.
- Solid brass plug blades are firmly embedded in body.
- See-through terminal cover and body allows inspection of connections.
- Terminals in individual chambers to positively insulate conductors.
- Clearly marked rating, NEMA configuration and standard compliances (third-party listing) on face of device.
- Terminal screws backed out - ready for wiring.
- Combination slot/Phillips head mounting and terminal screws ease installation with power screwdrivers. (Slot/Robertson screws in Canada where available).

INDUSTRIAL  
 COMMERCIAL  
 RESIDENTIAL

## I-4 STRAIGHT BLADE PLUGS AND CONNECTORS

#### Hospital Grade Plugs and Connectors

Rating		Cord		Body		Catalog No.	
A	V/AC	NEMA	Description	Diameter	Color	Plug	Connector
15	125	5-15	Straight	0.25 -0.69" (6.4-17.5mm)	Clear	8266	8269
20	125	5-20	Straight	0.25 -0.69" (6.4-17.5mm)	Clear	8366	8369
15	250	6-15	Straight	0.25 -0.69" (6.4-17.5mm)	Clear	8666	8669
20	250	6-20	Straight	0.25 -0.69" (6.4-17.5mm)	Clear	8466	8469



#### TESTING & CODE COMPLIANCE

- Listed to UL 498 (file no. E15012)
- UL verified to Federal Spec. WC-596.
- CSA Certified, (file no. 2081 (6221-02)).
- to C22.2 no 42.
- NOM Certified.

#### MATERIAL CHARACTERISTICS

Polycarbonate and PVC  
 Environmental:  
 Meets flammability requirements per UL 94, V2 rated.  
 Temperature Rating:  
 -20°C to 60°C.

