

## Hospital Grade Plugs and Connectors

2 Pole, 3 Wire Grounding  
NEMA 5-15, 15A 125V  
NEMA 5-20, 20A 125V



### AutoGrip™ Nylon Plugs and Connectors

#### FEATURES

- Neoprene gasket seals cord hole opening
- Automatic cord grip assembly clamps the flexible cord to reduce wiring time
- All thermoplastic construction reduces breakage.
- Combination head screws: U.S. Phillips/slotted; Canadian Robertson/slotted.
- Back wired Dead-Front design.
- Add "-C" to catalog numbers for Canadian screws.

#### AutoGrip™ Plugs and Connectors

Rating		NEMA	Description	Cord Diameter	Body Color	Catalog No.	
A	V/AC					Plug	Connector
15	125	5-15	Straight	0.300-0.656" (7.62-16.7mm)	Black & White	5266NHG	5269NHG
			Straight	0.300-0.656" (7.62-16.7mm)	Clear	5266NHGC	5269NHGC
			Straight Isolated Ground	0.300-0.656" (7.62-16.7mm)	Orange	IG5266NHG	—
20	125	5-20	Straight	0.300-0.656" (7.62-16.7mm)	Black & White	5366NHG	5369NHG*
			Straight	0.300-0.656" (7.62-16.7mm)	Clear	5366NHGC	5369NHGC*

\* Not CSA certified



5266NHGC



5369NHGC

COMMERCIAL  
INDUSTRIAL  
INSTITUTIONAL

**F-8**  
HOSPITAL GRADE  
DEVICES

#### TESTING & CODE COMPLIANCE

- Listed to UL 498 (file no. E3663),
- UL verified to Federal Spec. WC-596F,
- CSA Certified to C22.2 no. 42 (file no. LR7087), except as noted.

#### MATERIAL CHARACTERISTICS

Nylon; clear devices are Nylon and polycarbonate.  
Temperature Rating: -40°C to 75°C.



5-20P



5-20R



5-15P



5-15R