OUTDOOR JACK ASSEMBLIES

SURFACE MOUNT BOX/JACKS



19316L7-4

- Removable mounting tabs
- Station wire entrance coupling contains neoprene bushing for added protection. Wire entrance available from top, bottom, or either side
- Conduit or pipe entrance can be made by removing the 1/2 inch threaded pipe nipple
- Housing is die cast aluminum with corrosion resistant finish

PART#	DESCRIPTION	*CORROSHIELD*	WIRING
19316L7-4	4-conductor, screw terminals		USOC
19316L7-4NS-RC	4-conductor, filled splice connectors	*CorroShield*	USOC
19316L7E-4	4-conductor, screw terminals, trap door		USOC
19316L7-6	6-conductor, screw terminals		USOC
STAR19316	1-port, designed for use w/SpeedStar modular connector (not included)		
19316-L4	Surface mount outdoor box and cover assembly only		

FLUSH MOUNT OUTDOOR JACKS



16152L8E-4

- Neoprene rubber gasket provides water-resistant seal on masonry, wood, or uneven surfaces
- Faceplate is constructed of aluminum with baked enamel finish

PART#	DESCRIPTION	WIRING
16152L7-4	4-conductor, screw terminals, includes outlet box	USOC
16152L7E-4	4-conductor, screw terminals, trap door, includes outlet box	USOC
16152L7-6	6-conductor, screw terminals, includes outlet box	USOC
16152L8-4	4-conductor, screw terminals, no outlet box	USOC
16152L8E-4	4-conductor, screw terminals, trap door, no outlet box	USOC
STAR16152	1-port, designed for use w/SpeedStar connector (not included)	
16152-L5	Cover assembly only	

FLOOR JACKS

Suttle's series of simplex and duplex floor jacks allows mounting in standard outlet boxes and tombstone-style outlets for under carpet cabling and mounting in overhead raceway. Color matched 860 faceplates must be ordered separately.

- Screw or 110 Type terminations available
- Simplex or Duplex

SIMPLEX FLOOR JACKS



105AF-xx

PART#	DESCRIPTION	WIRING
105AF-xx	8-conductor, 110 IDC terminals, non-keyed	568B

COLORS (-xx): Ivory = (50) Electrical Ivory = (52)

DUPLEX FLOOR JACKS



106BFD-xx



625B3EF450

PART#	DESCRIPTION	LABEL	WIRING
106AFD-xx	8-/8-conductor, 110 IDC terminals, non-keyed	LINE 1/LINE 2	568B
106BFD-xx	8/8-conductor, 110 IDC terminals, non-keyed/keyed	VOICE/DATA	568B
106BFDY-xx	8/8-conductor, 110 IDC terminals, non-keyed/keyed	VOICE/DATA	USOC

COLORS (-xx): Ivory = (50) Electrical Ivory = (52) White = (85)

PART#	DESCRIPTION	WIRING
625B3EF450	4/4-conductor, screw terminals, trap door	USOC

COLOR: Ivory