

P O R T A B L E C O R D A G E

2-Conductor

UL/CSA Types: SPT-1, SPT-2, SP-1 and HPN

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm
SPT-1 PVC Parallel Lamp Cord • UL/CSA Listed													
300V, 60°C • One conductor polarity ribbed													
	19122	250	76.2	6.3	2.8	Brown, White, Black, Silver-Gray	18 (42x34) bare	.032	.81	—	—	.110	2.79
		1000	304.8	21.0	9.5							x .207	x 5.26
	8888*	250	76.2	6.3	2.8	Brown, Ivory	18 (42x34) bare	.032	.81	—	—	.110	2.79
		U-1000	U-304.8	21.0	9.5	Brown, Gray						x .207	x 5.26
SPT-2 PVC Parallel Lamp Cord • UL/CSA Listed													
300V, 60°C • One conductor polarity ribbed													
	19123	250	76.2	7.8	3.5	Brown, White, Black	18 (42x34) bare	.049	1.24	—	—	.144 x .277	3.66 x 7.04
	19126	250	76.2	9.8	4.4	Brown, Black	16 (65x34) bare	.048	1.22	—	—	.155 x .299	3.94 x 7.59
SP-1 Rubber Parallel Lamp Cord • UL Listed													
300V, 60°C • One conductor polarity ribbed													
	19115*	250	76.2	7.5	3.4	Brown, Black	18 (41x34) bare	.035	.89	—	—	.123 x .227	3.12 x 5.77
HPN CPE Heater Cord • UL/CSA Listed													
300V, 90°C													
	19405	250	76.2	7.8	3.5	Black	18 (41x34) bare	.047	1.18	—	—	.140	3.56
		1000	304.8	30.0	13.6							x .276	x 7.01
	19404	250	76.2	9.5	4.3	Black	16 (105x36) bare	.047	1.18	—	—	.152	3.86
		1000	304.8	38.0	17.3							x .300	x 7.62

*Not CSA recognized.