



Surface-mounting by screwing the base box onto the support using 2 screws \varnothing 3-4 mm max.

Surface Mounting Socket Outlet, France/Belgium/Poland, 16 Amp, 2P + E, 250 Volt AC, Automatic Terminals (Capacity 2x 1.5 mm² to 2.5 mm²), Conductor Stripping 13 mm, Cordage Range \varnothing 4 mm to \varnothing 15 mm, Conduit Range \varnothing 16/20/25 mm, Weather Protected IP 55 IK 07 (Cover Closed), Standards: (France) NF C 61-314, CEBEC (Belgium) CEI 60884-1, BBJ (Poland) CEI 60884-1, Conform with NF C 15-100 (Shutter System)

NOTES:

(1) Materials

- Box, support : PP reinforced polypropylene
- Plate, shutter : ABS (Acrylonitrile Butadiene Styrene)
- Outlet gland : PP + SEBS (Styrene Ethylene Butadiene Styrene)
- Mechanism : PC (Polycarbonate)

Tolerance	Approved		Date		www.biagmbh.com Copyright © B-I-A GmbH, Germany		
	Updated	jup	Date	2007-04-19	B-I-A Vertriebs GmbH		
	Drawn	poko	Date	2007-03-21	www.biaonline.com info@biagmbh.com		
	Catalog No.	69731			P/N Line	124788	L1074
	Drawing No.	00335EN-00	Rev. A		Material	see Note (1)	Unit mm
					Scale		