

IP66 Modular Devices

■ Product Installation Examples



■ General Product Information



Complete range of switches and domestic socket outlets IP66 with plug inserted, sturdy and resistant to UV rays thanks to the use of high-strength technopolymers.

The electrical socket outlets are available in the main Italian and International standards.

All series devices are available for surface, flush or pole mounting.

Ideal for installations in gardens and other places with the presence of water and dust, as well as in the tertiary sector and in light industry.

■ Marking, Directives and Quality Marks



■ Product Combination Example



M95 Dimensions
Surface Mounting
Single: 95 x 95 mm
Double: 195 x 95 mm
Overall Height
Switches: 59 mm
Controls: 59 mm
Sockets: 97 mm

- 1374427** Socket Outlet according to AS/NZS 10 Amp.
- 1373211** Single Pole Two Way Switch
- 137102** Surface Mounting Two Gang Box

■ Behaviour with Chemical and Atmospheric Agents

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited resistance	Resistant	Limited resistance	Limited resistance	Resistant	Not resistant	Not resistant	Resistant	Limited resistance	Resistant

Resistance values to chemical agents have to be considered indicative. For further information and specific substances, contact the technical service.

■ Product Features

All Devices	Socket Outlets	Switches and Control Devices
<ul style="list-style-type: none"> • Body in polycarbonate resistant to impacts, chemical agents and UV rays • Captive stainless steel closing screws • Blank sides with drilling point marks • Integrated external fixing points 	<ul style="list-style-type: none"> • Tinted polycarbonate cover to view the inside • Availability of empty versions to be fitted with EVOLUTION Series modules • Cable sleeve gaskets to maintain the IP66 degree of protection even with the plug inserted • Snap-on wing for cover opening and closing operations • British Standard models available with integrated DP switch 	<ul style="list-style-type: none"> • Status light indicator • Light locator frame (LEDs optional, not included) • XXL rocker to ensure operability in any situation • Under rocker gasket to guarantee IP66 degree in use conditions

Non stock products are procurement goods, can only be ordered in standard packaging quantities and have a minimum order value. The actual product may differ from the illustration shown. The information provided here is subject to change without notice. The product shown is for the use in the specified country.