

**Aluminum Flexible Conduit Type RWA**

	<p>Lightweight aluminum Smooth inside and outside Strong construction</p> <p>Size range: 3/8" to 2"</p> <p>UL listed</p> <p>Small bend radius for tight installations Meets requirements of UL # 1</p> 
---	--

Size	StockCode	Description	EDP#	Packaging	Wtg/100ft
3/8	441503	RWA 3/8"C		100 Feet Per Coil	6.5 lbs
3/8	441507	RWA 3/8"R		1000 Feet Per Reel	6.5 lbs
1/2	441513	RWA 1/2"C	121697	100 Feet Per Coil	9.5 lbs
1/2	441517	RWA 1/2"R		1000 Feet Per Reel	9.5 lbs
3/4	441523	RWA 3/4"C		100 Feet Per Coil	12.5 lbs
3/4	441526	RWA 3/4"R		500 Feet Per Reel	12.5 lbs
1	441532	RWA 1"C		50 Feet Per Coil	20 lbs
1-1/4	441542	RWA 1-1/4"C		50 Feet Per Coil	24 lbs
1-1/2	441551	RWA 1-1/2"C		25 Feet Per Coil	28 lbs
2	441561	RWA 2"C		25 Feet Per Coil	41 lbs