


ELECTROMAGNETIC BALLASTS

Straight
Rapid Start Lamps




HIGH POWER FACTOR SOUND RATED A

Lamp Data		Min. Starting Temp. (F)	Input Volts	Catalog Number	Certifications				Line Current (Amps)	Input Power ANSI (Watts)	Ballast Factor	THD %	Power Factor	Dim.	Wiring Dia.
Number	Watts				UL	CSA	E	RoHS							
F17T8 (265mA)															
1	17	50	120	R-1P817-TP	✓	✓		0.21	24	1.01	<20	0.95	T-2	20	
			277	V-1P817-TP	✓			0.10	26	1.04	<20	0.94			
2	17	50	120	R-2P817-TP	✓	✓		0.40	47	0.96	<15	0.98	T-2	21	
			277	V-2P817-TP	✓			0.17	45	0.98	<20	0.96			
F25T8 (265mA)															
1	25	50	120	R-1P825-TP	✓	✓		0.28	31	0.94	<25	0.92	T-2	20	
			277	V-1P825-TP	✓			0.12	30	0.91	<20	0.91			
2	25	50	120	R-2P825-TP	✓	✓		0.53	62	0.97	<15	0.97	T-2	21	
			277	V-2P825-TP	✓			0.23	62	0.96	<20	0.97			
F32T8 (265mA)															
1	32	50	120	R-1P32-TP Mark III	✓	✓		0.32	35	0.95	<15	0.91	T-2	20	
			277	V-1P32-TP Mark III	✓	✓		0.16	41	0.98	<15	0.93			
			347	G-1S32-TP Mark III		✓		0.12	41	0.98	<15	0.98			
2	32	50	120	R-2P32-TP Mark III	✓	✓	✓	0.61	71	0.99	<10	0.97	T-2	21	
			277	V-2P32-TP Mark III	✓	✓	✓	0.29	76	0.95	<10	0.95			
			347	G-2S32-TP Mark III		✓	✓	0.23	77	0.98	<15	0.96			
F40T8 (265mA)															
1	40	50	120	R-1P840-TP	✓	✓		0.45	52	1.02	<20	0.96	T-2	20	
			277	V-1P840-TP	✓			0.19	50	0.99	<20	0.95			
2	40	50	120	R-2P840-TP	✓	✓		0.73	87	0.87	<15	0.99	T-2	21	
			277	V-2P840-TP	✓			0.31	86	0.88	<15	0.99			



Diag. 20



Diag. 21

DIMENSIONS

Designation	Length (L) (inches)	Width (W) (inches)	Height (H) (inches)	Mounting (M) (inches)
T-2	9½	2¾	1½	8 ²⁹ / ₃₂

