



Straight Blade Devices
15 and 20 Ampere, 125 Volts
 2 Pole, 3 Wire Grounding



5278C-H



15A 125V
NEMA 5-15P
UL CSA




20A 125V
NEMA 5-20P
UL CSA


Flanged Inlets

Description	Catalog Number	
Nylon casing, back wired.	5278C-H	5378C-H
Weatherproof, gray, with lift cover and multiple drive screws.	61CM64-H	—
Weatherproof, black, with lift cover and boot, multiple drive screws.	61CM64BK-H	—
Stainless steel flange, phenolic body, miniature style, for molded on connectors only, multiple drive screws.	5240-H*	—


Note: *Specially designed to accept "molded-on" connector bodies. Catalog number 5240-H will not accept re-wireable size connector bodies listed in this catalog or molded connectors having a "rejection obstruction" as required by Underwriters Laboratories Inc. standard #817 cord sets and power supply cords" effective 7/1/81.



61CM64-H



5279C-H



15A 125V
NEMA 5-15R
UL CSA
0.5 HP




20A 125V
NEMA 5-20R
UL CSA
1 HP


Flanged Receptacles

Description	Catalog Number	
Nylon casing, back wired.	5279C-H	5379C-H
Stainless steel flange, phenolic body, covered terminals, multiple drive screws.	5279-H	—
Stainless steel flange, brown phenolic (mounting screws packed separately).	5256-H	—
Weatherproof, gray nylon, with lift cover and boot, multiple drive screws.	—	61CM65-H**

Note: **Not CSA Certified.



5256-H



61CM65-H

Dimensions in Inches (mm)