

Commercial Pressure Switches

Type F—PUMPTROL® Water Pump Pressure Switches—Class 9013



- Designed for the control of electrically driven water pumps.
- Type FSG is the standard water pump switch, suitable for all types of pumps: jets, submersible, reciprocating, etc.
- Type FYG is designed to meet higher horsepower and pressure requirements.
- Type FRG is reverse acting: contacts open on falling pressure.
- Diaphragm actuated.
- See page reference below for the following:
 - Electrical Ratings 20-26
 - Dimensions 20-13
 - Repair Parts Kits 20-10

Pressure Codes

Below is the pressure code table for standard action devices. Existence of a code does not imply that that code is available for any or all devices.

Settings	Code
5-21 psi	J15
8-20 psi	J16
20-40 psi	J20
20-50 psi	J18
30-50 psi	J21
40-60 psi	J24
50-70 psi	J33
55-85 psi	J34
60-80 psi	J25
Specify other pressure	J99

Pressure Codes (Reverse action)

Below is the pressure code table for reverse action devices. Existence of a code does not imply that that code is available for any or all devices.

Settings	Code
8.5-5.5 psi	J17
10-5 psi	J36
22-12 psi	J22
22-16 psi	J19
35-20 psi	J70
40-20 psi	J23
50-30 psi	J35
80-60 psi	J32
100-80 psi	J51
150-120 psi	J64
Specify other pressure	J99

Ordering Information

1. Specify Class 9013 Type F.
2. Select pressure code from Pressure Code Table above and add code designation to end of type number. Be sure that the pressure code falls within the limits of the device as shown in the device listings.
3. If special features are desired, add the appropriate Form letter to the Class and Type. Arrange Form letters in alphabetical sequence when ordering more than one special feature.
4. Place packaging code in alphabetical sequence with other forms when ordering.

For standard pack of 20 devices per box C20+
 For individually packaged devices leave blank††

Note: If no packaging code is indicated, devices will be shipped individually packaged.



File E12158 CCNKPZ



File LR25490

Selection Tables

Standard Action: Contacts Open On Rising Pressure

Cut-Out Range (psig)	Approximate Adjustable Differential (psig)	Cut-in Range (psig)	Pressure Connection	2 Pole			
				NEMA Type 1	Price	NEMA Type 3R▲	Price
20-65	15-30	10-45	1/8" NPSF Internal	FSG1		FSW1	
			1/4" NPSF Internal	FSG2		FSW2	
			1/4" NPT External	FSG9		FSW9	
			1/4" Bayonet (barbed)	FSG10		FSW10	
20-50	10-30	10-30	1/4" NPSF Internal	FSG22		FSW22	
			1/4" NPT External	FSG29		FSW29	
			1/4" NPSF Internal	FSG42		FSW42	
			1/4" NPT External	FSG49		FSW49	
34-65	15-30	19-45	(FSG120 WITH FORM M4)				
25-80	20-30	5-60	1/8" NPSF Internal	FYG1		FYW1	
			1/4" NPSF Internal	FYG2		FYW2	
			1/4" NPT External	FYG9		FYW9	
			1/4" Bayonet (barbed)	FYG10		FYW10	
39-80	20-30	19-60	90° Elbow 1/4" Bayonet	FYG20		FYW20	
			(FYG120 WITH FORM M4)				
			1/4" NPSF Internal	FYG22		FYW22	
			1/4" NPT External	FYG29		FYW29	
20-50	10-30	10-30	1/4" NPSF Internal	FYG42		FYW42	
			1/4" NPT External	FYG49		FYW49	
			1/4" NPSF Internal	FYG22		FYW22	
			1/4" NPT External	FYG29		FYW29	
9-40	6-20	3-10	1/4" NPSF Internal	FYG42		FYW42	
			1/4" NPT External	FYG49		FYW49	

Reverse Action: Contacts Open On Falling Pressure

Cut-in Range (psig)	Approximate Adjustable Differential (psig)	Cut-Out Range (psig)	Pressure Connection	1-Pole		2-Pole	
				Type	Price	Type	Price
23-65	15-30	8-45	1/4" NPSF Internal	FRG12		FRG2	
			3/8" NPSF Internal	FRG13		FRG3	
			1/4" Flare	FRG18		FRG8	
			1/4" NPT External	FRG19		FRG9	
10-45	6-20	4-25	1/4" NPSF Internal	FRG32		FRG22	
			3/8" NPSF Internal	FRG33		FRG23	
			1/4" Flare	FRG38		FRG28	
			1/4" NPT External	FRG39		FRG29	
6-14	5 Non-adjustable	1-9	1/4" NPSF Internal	FRG52		FRG42	
			3/8" NPSF Internal	FRG53		FRG43	
			1/4" Flare	FRG58		FRG48	
			1/4" NPT External	FRG59		FRG49	
40-100	20-30	20-75	1/4" NPSF Internal	FRG72		FRG62	
			3/8" NPSF Internal	FRG73		FRG63	
			1/4" Flare	FRG78		FRG68	
			1/4" NPSF Internal	FRG92		FRG82	
65-150	30-45	35-120	3/8" NPSF Internal	FRG93		FRG83	
			1/4" Flare	FRG98		FRG88	
			1/4" NPT External	FRG99		FRG89	

▲ Must be mounted in vertical position to maintain enclosure rating.

Special Features and Modifications for Type FSG, FYG & FRG Devices

Description	Applies to	Form Letter	Price Addition
Standard Pack of 20 Devices per box	All Type F	C20	N/C
Pilot Light—Indicates Switch Contacts Closed	FSG, FYG	G5■	
One Normally Open—One Normally Closed Contact	FRG 2-Pole Only	H	
Maintained Manual Cut-Out Lever (AUTO-OFF)	FSG, FYG	M1	
Momentary Manual Cut-In Lever (AUTO-START)	FRG2-59 Only	M3	
Low Pressure Cut-Off (AUTO-START-OFF) Operates at Approximately 10 psig Below Cut-in and will turn off the pump	FSG, FYG	M4	
Maintained Manual Cut-in Lever (AUTO-ON)	FRG2-59 Only	M5	
Pulsation Plug (Type 2 & 9 Only)	FRG, FSG, FYG	P■	
Salt Water Flange (1/4" NPSF Internal Only)	All Type F	Q	
Plastic Flange (max. temp. 120°F) (max. pressure 80 psi)	FSG, FYG, FRG	Q8	
	1/4" NPSF Internal Only		
1/2" Conduit Bushing—1/2" Long Thread—on Left	All Type F	T	
1/2" Conduit Bushing—1/2" Long Thread—on Right	All Type F	T1	
Slip-On Connectors (Load Side Terminals Only)	FSG, FYG	U	
Slip-On Connectors (Line and Load Terminals)	FSG, FYG	U2	
Black Cover	FSG, FYG	Z22	N/C

- Can be field installed. Nameplate should then be marked with the Form letter and maintenance and ordering records corrected.
- ◆ Nylon pulsation plug can be field installed on types having 1/4" NPSF Internal connector. Part number 1530S6G1 is one bag of 50 plugs.