

ETR Series

Portable Safety Transformers

Ortsveränderliche Trenntransformatoren

OPTIONS TABLE

Further Configurations available

Weitere Konfigurationen lieferbar

Key	Description	Ref. Catalog No.
Primary (Input): Germany, Secondary (Output): Germany		
A00	Input: Detachable Cord 2x1.5mm ² , Length 1.5m, Straight SCHUKO Rubber Plug Output: One SCHUKO 16A Standard Socket (IP20)	1439190 386BL



1439190
(max. 3 x 1.5 mm²)



1149290
(max. 3 x 2.5 mm²)



386BL
(IP 20)



496BL
(IP 44)

ETR Series

Portable Safety Transformers

Ortsveränderliche Trenntransformatoren

OPTIONS TABLE

Further Configurations available

Weitere Konfigurationen lieferbar

Key	Description	Ref. Catalog No.
Primary (Input): without Plug (open End), Secondary (Output): Germany		
A50	Input: Detachable Cord 2x1.5mm ² , Length 2.0m, with AE-Terminals (open End) Output: One SCHUKO 16A Standard Socket (IPX4)	N/A 496BL
A51	Input: Detachable Cord 2x2.5mm ² , Length 2.0m, with AE-Terminals (open End) Output: One SCHUKO 16A Standard Socket (IPX4)	N/A 496BL



515PV
(NEMA 5-15P)



520PV
(NEMA 5-20P)



386BL
(IP 20)



496BL
(IP 44)

ETR Series

Portable Safety Transformers

Ortsveränderliche Trenntransformatoren

OPTIONS TABLE

Further Configurations available

Weitere Konfigurationen lieferbar

Key	Description	Ref. Catalog No.
Primary (Input): Germany, Secondary (Output): USA/Canada		
B00	Input: Cord 2x1.5mm ² , Length 2.0m, Straight 2-Pole (Kontur) Plug CEE 7/17 (10/16A 250V) Output: Single Wet Location U.S.A. Receptacle (IPX4), NEMA 5-15R	K6A-5 UL12505
B01	Input: Cord 2x1.5mm ² , Length 2.0m, Straight 2-Pole (Kontur) Plug CEE 7/17 (10/16A 250V) Output: Single Wet Location U.S.A. Receptacle, NEMA 5-15R	K6A-5 5185-0
B02	Input: Cord 2x1.5mm ² , Length 2.0m, Straight 2-Pole (Kontur) Plug CEE 7/17 (10/16A 250V) Output: Single Panel Mounting U.S.A. Receptacle, NEMA 5-15R	K6A-5 817-2B
B03	Input: Cord 2x1.5mm ² , Length 2.0m, Straight 2-Pole (Kontur) Plug CEE 7/17 (10/16A 250V) Output: Duplex Flush Mounting U.S.A. Receptacle, NEMA 5-15R Duplex Wet Location Cover Plate	K6A-5 5320-CP 4970 022
B04	Input: Cord 2x1.5mm ² , Length 1.5m, Straight 2-Pole (Kontur) Plug CEE 7/17 (10/16A 250V) Output: Single Wet Location U.S.A. Receptacle, NEMA 5-15R	K6A-5 5185-0
B05	Input: Detachable Power Supply Cord 2x2.5mm ² , Length 2.4m, Straight 2-Pole (Kontur) Plug CEE 7/17 (10/16A 250V) Output: Single Flush Mounting U.S.A. Receptacle, NEMA 5-20R Single Wet Location Cover Plate	N/A 5801-I 5091-0
B06	Input: Detachable Power Supply Cord 2x2.5mm ² , Length 2.0m, Straight 2-Pole (Kontur) Plug CEE 7/17 (10/16A 250V) Output: Single Flush Mounting U.S.A. Receptacle, NEMA 5-20R Single Wet Location Cover Plate	N/A 5801-I 5155-0



K6A-5
(max. 2 x 1.5 mm²)



817-2B
(NEMA 5-15R)



5185-0
(Wet Location)



UL12505
(IP 44)

ETR Series

Portable Safety Transformers

Ortsveränderliche Trenntransformatoren

OPTIONS TABLE

Further Configurations available

Weitere Konfigurationen lieferbar

Key	Description	Ref. Catalog No.
Primary (Input): USA/Canada, Secondary (Output): Germany		
C00	Input: Cord Length 2.0m, Straight U.S.A. Plug NEMA 5-15P Output: Single SCHUKO 16A Standard Socket	113 496BL
C01	Input: Cord Length 1.5m, Straight U.S.A. Plug NEMA 5-15P Output: Single SCHUKO 16A Standard Socket	113 496BL
C02	Input: Cord Length 15.0m H07RN-F2x2.5mm ² , Straight U.S.A. Plug NEMA 10-20P Output: Single SCHUKO 16A Standard Socket	2836 496BL
C03	Input: Cord Length 2.0m, Straight U.S.A. Plug NEMA 5-15P Output: Single SCHUKO 16A Standard Socket	515PR 496BL
C04	Input: Detachable Cord, Length 2.0m, H07RN-F 2x1.5mm ² , Straight U.S.A. Plug NEMA 5-15P Output: Single Wet Location (IP X4) SCHUKO 16A Standard Socket	515PR 496BL
C05	Input: Cord Length 1.8m, Straight U.S.A. Plug NEMA 5-15P Output: Single SCHUKO 16A Standard Socket	113 496BL
C06	Input: Cord Length 5.0m, Straight U.S.A. Plug NEMA 5-15P Output: Single SCHUKO 16A Standard Socket	515PR 496BL
C07	Input: Detachable Cord 2x1.5mm ² , Length 2.0m, Straight U.S.A. Plug NEMA 5-20P Output: Single SCHUKO 16A Standard Socket (IP X4)	520PV 496BL
C08	Input: Power Supply Cord, Length 2.4m SJT 14/3, Straight U.S.A. Plug NEMA 5-15P Output: One Single Wet Location (IP X4) SCHUKO 16A Standard Socket	4400-08F-BB 496BL
C09	Input: Power Supply Cord, Length 2.4m SJT 14/3, Straight U.S.A. Plug NEMA 5-15P Output: Two Single Wet Location (IP X4) SCHUKO 16A Standard Sockets	4400-08F-BB 496BL
C10	Input: Cord Length 1.8m, Straight U.S.A. Plug NEMA 5-20P Output: Single SCHUKO 16A Standard Socket (IP X4)	520PV 496BL



113
(NEMA 5-15P)



515PR
(NEMA 5-15P)



520PV
(NEMA 5-20P)



496BL
(IP 44)

ETR Series

Portable Safety Transformers

Ortsveränderliche Trenntransformatoren

OPTIONS TABLE

Further Configurations available

Weitere Konfigurationen lieferbar

Key	Description	Ref. Catalog No.
Primary (Input): USA/Canada, Secondary (Output): United Kingdom		
D00	Input: Cord Length 2.0m, Straight U.S.A. Plug NEMA 5-15P Output: Single Wet Location (IP 44) Socket Outlet United Kingdom BS 1363	113 4080GRY
Primary (Input): Japan, Secondary (Output): Germany		
E00	Input: Cord Length 2.0m, Straight Japan Rubber Plug 15A/125V AC Output: Single SCHUKO 16A Standard Socket	5-15P Configuration 496BL



113
(NEMA 5-15P)



515PR
(NEMA 5-15P)



4080GRY
(13A/250V)



496BL
(IP 44)