



Wiring Devices, France / Belgium

230V/50Hz; 10A - 16A max.

France and Belgium have a standard socket which is **not** compatible with the CEE 7 socket that is standard in Germany and other continental European countries. The reason for incompatibility is that grounding in the French / Belgian socket is accomplished with a round male pin permanently mounted in the socket. The **CEE 7/7** plug bridges the difference between the two types of sockets. It has grounding clips on both sides to mate with the CEE 7 socket and a female contact to accept the grounding pin of the French / Belgian socket. Note that the CEE 7/7 plug is polarised when used in the French and Belgian electrical system.

France / Belgium Cord-Sets are available on request.

Document	Catalog No. / Katalog-Nr.	Description / Beschreibung	Weight/ea	VPE/Pack	U/M	EDP-No.
2537 2536	Modular Snap-In Socket Outlets					
	74116	Modular Snap-In Socket Outlet, White, with Protective Cover	43g	50/10	ea	114172
	74111	Modular Snap-In Socket Outlet, White	36g	200/10	ea	112908
<p>French standard modular snap-in socket outlets, 2-pole 3-wire grounding (2P+E), with earthing pin Ø 4.8 mm, 10/16 Amp, 250Vac, white, with protective shutters, used with clip mounting frame #74852 or with DIN-Rail modular mounting frame #74872, conform with NF C 15-100 for the protection of children.</p> <p>Further items and informations can be found in documents indicated.</p>						
2538 2314 9031	Modular Clip Mounting Frame and Modular DIN-Rail Mounting Frame					
	74852	Modular Clip Mounting Frame, White	15g	100/10	ea	114173
	74872	Modular DIN-Rail Mounting Frame, White, CE	17g	100/10	ea	112911
<p>35mm DIN-Rail Mounting Modular Support Mechanisms for symmetrical DIN-Rail used with modular sockets or other mechanisms, frame width 46.3 mm.</p> <p>Further informations can be found in documents indicated.</p>						
2540 2539	Surface Mounting Receptacles					
	91644	Weather Protective Surface Socket Outlet, IP 55, Grey, CE	110g	100/10	ea	112949
	83027	Standard Surface Socket Outlet, White	56g	100/10	ea	108509
<p>French standard surface socket outlet, 2-pole 3-wire grounding (2P+E), with earthing pin Ø 4.8 mm, 10/16 Amp, 250Vac, white, with protective shutters.</p> <p>Further informations can be found in documents indicated.</p>						
2541	Multi-Outlet Extension Strip					
	50525	3-Way Outlet-Strip, White, with Indicator Lamp	244g	20	ea	108511
<p>French standard multi-outlet extension strips, 2-pole 3-wire grounding (2P+E), with earthing pin Ø 4.8 mm, 10/16 Amp, 230Vac, white, with power supply cord 1.5 m length, with protective shutters, conform to NF C 61-601 for pins Ø 4 mm and 4.8 mm.</p> <p>Further versions (3-, 4- and 6-way) and informations can be found in document indicated.</p>						
2444 2542	Mains Line Plugs, France and Belgium					
	616 WH	Mains Line Plug, White, VDE / CEBEC Combination Earthing System	48g	50	ea	110291
	50216	Angle Plug, White, NF (France/Belgium), with Side Cable Entry	27g	200/20	ea	114690
<p>French standard angle plug, 2-pole 3-wire grounding (2P+E), with earthing pin socket Ø 4.8 mm, 10/16 Amp, 250Vac, white, Ø 35 mm base, for class I appliances, for circular cable max. Ø 11 mm.</p> <p>Further colors, items and informations can be found in documents indicated.</p>						
2445	Flush Mounting Socket Outlet, France / Belgium Version					
	497 BK	Flush Mount Socket Outlet, Black, with Hinged Self-Closing Lid	41g	35	ea	115522
	096	Gasket, OPTIONAL, (60x48)mm	2g	100/25	ea	112945
<p>Flush mounting socket outlet with earthing pin, France / Belgium version, with hinged self-closing lid, distance between fixing centers 38 mm, thermoplastic, black.</p> <p>Further colors, items and informations can be found in document indicated.</p>						