

Australian Mains Plug Tops and Extension Sockets

Plugs with AS/NZS 3112:2000 Insulated Pins

Rewirable plug tops incorporating models with large finger grips and impact-resistant materials (90 series), flexible covers (100 series) or low-profile side entry for space saving (106 series).

For extension leads. The 10A versions have a molded safety skirt to prevent accidental contact with live conductors on partly pulled-apart plugs.



The latest publication of Australian Standard AS/NZS 3112:2000 for Australian Mains Plugs introduced requirements for the insulation of the Active and Neutral pins of plugs. These requirements were introduced in response to a number of incidents including fatalities involving plugs and plug-in devices involving a metal object (such as a metal blind slat or sheet of metal) coming into contact with a plug pin that was partially removed from a socket and resulted in an electrical shock.

From 3 April 2005 insulated live pins will be mandatory for all plugs (and appliances with integral pins). Approval of non-insulated pins will be cancelled on that date. In the interests of enhanced electrical safety and to ensure rapid dispersion into the marketplace, each Australian State and Territory and New Zealand Electrical Regulator will require all electrical equipment to be supplied with insulated pin plugs, at all points of sale, by no later than 3 April 2005.



RCM (Regulatory Compliance Mark): signifies that a product meets relevant electrical safety and Electromagnetic Compatibility (EMC) requirements.



Quality logo: Used to signify that a product is manufactured under a quality system certified as complying with ISO/AS9002 by an accredited certification body.

To learn more about B-I-A please visit us at our
WEB site: www.BiaGmbH.com



PLUG TOPS

Rewirable plug tops incorporating models with large finger grips and impact-resistant materials (90 series), flexible covers (100 series) or low-profile side entry for space saving (106 series).

There's even an 'ezy-pull' model approved by the arthritis foundation



Additional features	Ezy-pull plug top (pictured) is approved by the Arthritis Foundation of Australia.
Available in	See product details
Voltage	250V ac
Frequency	50 Hz
Current	100 series: 10A, 15A; 90 series: 10A, 15A, 20A, 25A; 106 series: 10A, 15A, 20A, 25A, 32A

Colours



white



dark grey



black



clear CL
(100L only)



Quality Endorsed Company



Large finger-grip, rigid, impact-resistant moulding, 250V ac

Available in White (WE), Grey (GY) & Black (BL).

Item code	Description
90	10A plug top, 3 pin flat
90/15	15A plug top, 3 pin flat
90/20	20A plug top, 3 pin flat
90/25	25A plug top, 3 pin, L-shaped earth, flat active and neutral
90R	10A plug top, 3 pin, round earth, flat active and neutral
90/2R	10A plug top, 3 pin, flat earth, round active & neutral
94	10A plug top, 4 pin plug for use with 33 and 34 series. Available in white only.



Flexible PVC cover with cord locking nut, and screwed clamp terminals, 250V ac

Available in White (WE), Grey (GY), Black (BL) & Clear (CL).

Item code	Description
100L	10A plug top, 3 pin flat, locking nut, 8mm entry hole
100LHD	10A plug top, 3 pin flat, 10mm entry hole for 15A heavy duty cord
100/8	10A plug top, 3 pin flat, figure 8 wire
100R	10A plug top, 3 pin, round earth, flat active & neutral
100/2R	10A plug top, 3 pin, flat earth, round active & neutral
100L15	15A plug top, 3 pin flat



Low profile side entry with 45° cord entry and screwed clamp terminals, 250V ac

Available in White (WE), Grey (GY) & Black (BL).

Item code	Description
106/1	10A plug top, 3 pin flat.
106/1A	10A plug top, 3 pin flat, Ezy-Pull slide-on handle & locking base
106/2	10A plug top, 3 pin flat, accepts 15A heavy duty flexible cord.
106/3	15A plug top, 3 pin flat
106/4	20A plug top, 3 pin flat
106/5	25A plug top, 3 pin, L-shaped earth, flat active and neutral
106/6	10A plug top, 3 pin, round earth, flat active & neutral
106/7	10A plug top, 3 pin, flat earth, round active & neutral
106/8	32A plug top, 3 pin, U-shaped earth, flat active & neutral

EXTENSION SOCKETS

For extension leads. The 10A versions have a molded safety skirt to prevent accidental contact with live conductors on partly pulled-apart plugs.



Additional features	Insulating skirt for maximum safety
Available in	Standard and heavy-duty versions, 10A and 15A.
Configuration	3-pin flat
Additional accessories	cordlock Cat. D107 can be used to prevent two extension leads pulling apart.
Voltage	240V ac
Frequency	50 Hz
Current	10A, 15A

Colours



white



dark grey



clear

clear



Quality Endorsed Company



Flexible PVC cover with safety skirt, cord locking nut and screwed clamp terminals, 250V ac

Available in White (WE), Grey (GY), Black (BL) & Clear (CL).

Item code	Description
7P	10A extension socket, 3 pin flat, 8mm entry hole
7PHD	10A extension socket, 3 pin flat, suitable for H/Duty cable
7P15	15A extension socket, 3 pin flat, 10mm entry hole



Large finger grip, rigid, impact resistant moulding, separate cord clamp bar, cord guard, 250V ac

Available in White (WE) & Grey (GY).

Item code	Description
10/15	15A extension socket, 3 pin flat
10/10*	10A extension socket, 3 pin flat (white only)

* If current stock is depleted item will be discontinued

To learn more about B-I-A please visit us at our
WEB site: www.BiaGmbH.com

